

Package ‘billboarder’

September 9, 2024

Title Create Interactive Chart with the JavaScript 'Billboard' Library

Version 0.5.0

Description Provides an 'htmlwidgets' interface to 'billboard.js', a re-usable easy interface JavaScript chart library, based on D3 v4+. Chart types include line charts, scatterplots, bar/lollipop charts, histogram/density plots, pie/donut charts and gauge charts. All charts are interactive, and a proxy method is implemented to smoothly update a chart without rendering it again in 'shiny' apps.

URL <https://github.com/dreamRs/billboarder>,
<https://dreamrs.github.io/billboarder/>

BugReports <https://github.com/dreamRs/billboarder/issues>

Depends R (>= 3.1.0)

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.3.2

Imports htmlwidgets, htmltools, magrittr, jsonlite, ggplot2, scales, shiny, rlang

Suggests RColorBrewer, testthat, knitr, rmarkdown, covr

VignetteBuilder knitr

NeedsCompilation no

Author Victor Perrier [aut, cre],
Fanny Meyer [aut],
NAVER Corp [cph] (billboard.js library),
Mike Bostock [cph] (d3.format library)

Maintainer Victor Perrier <victor.perrier@dreamrs.fr>

Repository CRAN

Date/Publication 2024-09-09 19:00:21 UTC

Contents

billboarder-package	3
avengers	4
bauge	5
bauge-shiny	7
bb_add_style	7
bb_area	8
bb_axis	9
bb_bar	10
bb_barchart	10
bb_bar_color_manual	12
bb_bubble	13
bb_callbacks	14
bb_categories	15
bb_color	16
bb_colors_manual	17
bb_data	18
bb_densityplot	19
bb_donut	20
bb_donutchart	21
bb_export	22
bb_gauge	23
bb_gaugechart	24
bb_grid	25
bb_histogram	26
bb_interaction	28
bb_labs	29
bb_legend	30
bb_line	31
bb_linechart	31
bb_load	34
bb_lollipop	35
bb_padding	36
bb_pie	37
bb_piechart	38
bb_point	39
bb_proxy_axis_labels	39
bb_proxy_data_colors	40
bb_proxy_data_names	41
bb_proxy_flow	43
bb_proxy_focus	44
bb_proxy_groups	46
bb_proxy_hide	46
bb_proxy_legend	47
bb_proxy_show	49
bb_proxy_tooltip	50
bb_proxy_transform	50

bb_proxy_xs	51
bb_radar	51
bb_radarchart	52
bb_regions	53
bb_render	55
bb_scatterplot	56
bb_spline	57
bb_subchart	57
bb_svg	58
bb_title	59
bb_tooltip	59
bb_transition	60
bb_treemap	61
bb_treemapchart	61
bb_unload	62
bb_zoom	63
billboard-aes	63
billboard-theme	65
billboarder	66
billboarder-exports	66
billboarder-shiny	67
cdc_prod_filiere	69
equilibre_mensuel	70
prefix	70
prod_filiere_long	71
prod_par_filiere	71
proxy_example	72
suffix	73
Index	74

billboarder-package *An htmlwidget interface to the billboard.js javascript chart library*

Description

This package allow you to use billboard.js (<https://naver.github.io/billboard.js/>), a reusable easy interface JavaScript chart library, based on D3 v4+.

Author(s)

Victor Perrier (@dreamRs_fr)

See Also

Useful links:

- <https://github.com/dreamRs/billboarder>
- <https://dreamrs.github.io/billboarder/>
- Report bugs at <https://github.com/dreamRs/billboarder/issues>

avengers

Power ratings for The Avengers.

Description

Data are available in "long" and "wide" format.

Usage

avengers

avengers_wide

Format

A data frame with 24 rows and 4 variables:

group Name of the hero

axis Power skill

value Value (1-7)

description Character description

An object of class `data.frame` with 6 rows and 5 columns.

Source

Marvel Wikia (https://marvel.fandom.com/wiki/Marvel_Database) and Chris Zhou (<http://bl.ocks.org/chrisrzhou/2421ac6541b68c1680f8>)

bauge*Simple Gauge*

Description

A gauge that automatically updates itself in Shiny apps.

Usage

```
bauge(  
  value,  
  min = 0,  
  max = 100,  
  colors = NULL,  
  steps = NULL,  
  label_tooltip = NULL,  
  label_show = TRUE,  
  label_format = NULL,  
  label_extents = NULL,  
  expand = TRUE,  
  subtitle = NULL,  
  full_circle = FALSE,  
  gauge_width = NULL,  
  width = NULL,  
  height = NULL,  
  elementId = NULL  
)
```

Arguments

<code>value</code>	Value for the gauge.
<code>min</code>	Minimal value for the gauge, default to 0.
<code>max</code>	Maximal value for the gauge, default to 100.
<code>colors</code>	Vector of color(s), if more than one, steps must be specified.
<code>steps</code>	Upper bound for changing colors.
<code>label_tooltip</code>	Label to appear on the tooltip, when mouse is hovering the gauge.
<code>label_show</code>	Show or not minimal and maximal labels.
<code>label_format</code>	JavaScript function to format inner label.
<code>label_extents</code>	JavaScript function to set custom labels.
<code>expand</code>	Enable or disable expanding gauge.
<code>subtitle</code>	Additional text to add below the value.
<code>full_circle</code>	Show full circle as donut. When set to TRUE, the max label will not be showed due to start and end points are same location.

gauge_width	Set width of gauge chart.
width	Width of the element container.
height	Height of the element container.
elementId	Use an explicit element ID for the widget.

Examples

```

bauge(45)

bauge(67, colors = "#F6C600")

bauge(90, full_circle = TRUE)

bauge(90, max = 210, gauge_width = 20, label_format = suffix(" km/h"))

# Shiny example
if (interactive()) {
  library(shiny)

  ui <- fluidPage(
    baugeOutput(outputId = "gauge", width = "300px"),
    actionButton(inputId = "update_value", label = "Update value"),
    actionButton(inputId = "update_max", label = "Update max")
  )

  server <- function(input, output, session) {

    value <- reactive({
      input$update_value
      round(sample.int(100, 1))
    })

    max_value <- reactive({
      input$update_max
      sample(100:200, 1)
    })

    output$gauge <- renderBauge({
      bauge(
        value = value(),
        max = max_value(),
        steps = c(30, 60, 90, 100),
        colors = c("#FF0000", "#F97600", "#F6C600", "#60B044")
      )
    })

  }

  shinyApp(ui, server)
}

```

`bauge-shiny`*Shiny bindings for bauge*

Description

Output and render functions for using bauge within Shiny applications and interactive Rmd documents.

Usage

```
baugeOutput(outputId, width = "100%", height = "200px")
renderBauge(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

<code>outputId</code>	output variable to read from
<code>width, height</code>	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
<code>expr</code>	An expression that generates a bauge
<code>env</code>	The environment in which to evaluate <code>expr</code> .
<code>quoted</code>	Is <code>expr</code> a quoted expression (with <code>quote()</code>)? This is useful if you want to save an expression in a variable.

`bb_add_style`*Add custom style for regions and grid lines*

Description

Add custom style for regions and grid lines

Usage

```
bb_add_style(
  bb,
  region = NULL,
  x_grid = NULL,
  y_grid = NULL,
  ...,
  .list = NULL
)
```

Arguments

bb	A billboard htmlwidget object.
region	A named list with style associated with region.
x_grid	A named list with style associated with grid line on the X-axis.
y_grid	A named list with style associated with grid line on the Y-axis.
..., .list	Used internally.

Value

A billboard htmlwidget object.

Examples

```
# Change default color for regions
billboarder() %>%
  bb_linechart(data = sin(seq(-pi, pi, length.out = 30))) %>%
  bb_regions(
    list(start = 0, end = 10, class = "custom"), # add custom class
    list(start = 19, end = 29, class = "foo")
  ) %>%
  bb_add_style(region = list(custom = "fill: red;", foo = "fill: #009246;"))

# Customize grid line and text
billboarder() %>%
  bb_linechart(data = sin(seq(-pi, pi, length.out = 30))) %>%
  bb_y_grid(lines = list(list(
    value = 0, text = "Zero", position = "middle", class = "zero"
  ))) %>%
  bb_add_style(y_grid = list(
    zero = list(line = "stroke: red", text = "font-size: 240%; fill: black"
  )))
```

bb_area

Area property for a Billboard.js chart

Description

Area property for a Billboard.js chart

Usage

```
bb_area(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.area

Value

A billboard htmlwidget object.

bb_axis	<i>Add axis parameters</i>
---------	----------------------------

Description

Add axis parameters

Usage

```
bb_axis(bb, ...)
```

```
bb_x_axis(bb, ...)
```

```
bb_y_axis(bb, ...)
```

Arguments

bb A billboard htmlwidget object.

... Arguments defined in <https://naver.github.io/billboard.js/demo/>.

Value

A billboard htmlwidget object.

Examples

```
stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer", "shinyWidgets", "visNetwork"),
  stars = c(9, 178, 43, 46, 175)
)

# Add a label to y axis
billboarder() %>%
  bb_barchart(data = stars) %>%
  bb_axis(y = list(label = list(text = "# of stars", position = "middle")))

# or shorter :
billboarder() %>%
  bb_barchart(data = stars) %>%
  bb_y_axis(label = list(text = "# of stars", position = "outer-top"))
```

bb_bar	<i>Bar property for a Billboard.js chart</i>
--------	--

Description

Bar property for a Billboard.js chart

Usage

```
bb_bar(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.bar

Value

A billboard htmlwidget object.

Examples

```
billboarder() %>%  
  bb_barchart(data = data.frame(v1 = c("a", "b", "c"), value = c(5, 6, 3))) %>%  
  bb_bar(width = list(ratio = 0.95))
```

bb_barchart	<i>Helper for creating a bar chart</i>
-------------	--

Description

Helper for creating a bar chart

Usage

```
bb_barchart(  
  bb,  
  data,  
  mapping = NULL,  
  stacked = FALSE,  
  rotated = FALSE,  
  color = NULL,  
  ...  
)
```

Arguments

bb	A billboard htmlwidget object.
data	A <code>data.frame</code> , the first column will be used for x axis unless specified otherwise in mapping. If not a <code>data.frame</code> , an object coercible to <code>data.frame</code> .
mapping	Mapping of variables on the chart, see bbaes .
stacked	Logical, if several columns are provided, produce a stacked bar chart, else a dodge bar chart.
rotated	Switch x and y axis position.
color	Bar's color.
...	Arguments for slot bar, see https://naver.github.io/billboard.js/release/latest/doc/Options.html#.bar .

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarderProxy](#) in shiny application.

Examples

```
stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer",
             "shinyWidgets", "visNetwork", "rAmCharts",
             "D3partitionR"),
  stars = c(67, 252, 160, 144, 224, 32, 25)
)

# By default, first column is mapped on the x-axis
# second one on the y axis
billboarder() %>%
  bb_barchart(data = stars)

# Specify explicitly the columns to use
billboarder() %>%
  bb_barchart(data = stars, mapping = bbaes(package, stars), rotated = TRUE)

# Add some options
billboarder() %>%
  bb_barchart(data = stars[order(stars$stars), ], x = "package", y = "stars", rotated = TRUE) %>%
  bb_data(names = list(stars = "Number of stars")) %>%
  bb_y_grid(show = TRUE)

# Hack stacked barcharts (to color bar)
```

```

stars_wide <- data.frame(
  author = c("dreamRs", "davidgohel", "davidgohel", "dreamRs",
            "datastorm-open", "datastorm-open", "AntoineGuillot2"),
  package = c("billboarder", "ggiraph", "officer",
            "shinyWidgets", "visNetwork", "rAmCharts",
            "D3partitionR"),
  stars = c(67, 252, 160, 144, 224, 32, 25)
)

billboarder() %>%
  bb_barchart(data = stars_wide,
             mapping = bbaes(package, stars, group = author),
             stacked = TRUE)

billboarder() %>%
  bb_barchart(data = stars_wide,
             mapping = bbaes(author, stars, group = package),
             stacked = TRUE)

# Grouping variable
tab <- table(sample(letters[1:5], 100, TRUE), sample(LETTERS[1:5], 100, TRUE))
dat <- as.data.frame(tab)

billboarder() %>%
  bb_barchart(data = dat, bbaes(x = Var1, y = Freq, group = Var2), rotated = TRUE)

# You can also pass data in a 'wide' format
dat2 <- data.frame(
  x = letters[1:5],
  A = sample.int(n = 100, size = 5),
  B = sample.int(n = 100, size = 5),
  C = sample.int(n = 100, size = 5),
  D = sample.int(n = 100, size = 5),
  E = sample.int(n = 100, size = 5)
)

# But cannot use mapping
billboarder() %>%
  bb_barchart(data = dat2, stacked = TRUE) %>%
  bb_data(order = NULL, labels = TRUE)

```

bb_bar_color_manual *Manual color for barchart*

Description

Manual color for barchart

Usage

```
bb_bar_color_manual(bb, values)
```

Arguments

bb	A billboard htmlwidget object.
values	A named vector, names represent the categories of the bar chart, values correspond to colors. All categories must be present in the vector, in the same order of the chart.

Value

A billboard htmlwidget object.

Note

Must be called after `bb_bar`.

Examples

```
## Not run:

library("data.table")
library("billboarder")

data("mpg", package = "ggplot2")
setDT(mpg)

# all in blue
manufa <- unique(mpg$manufacturer)
cols <- rep("#08298A", length(manufa))
names(cols) <- manufa

# Nissan in red
cols[["nissan"]] <- "#DF0101"

billboarder() %>%
  bb_barchart(data = mpg[, list(count = .N), by = manufacturer][order(count)]) %>%
  bb_bar_color_manual(values = cols)

## End(Not run)
```

bb_bubble

Bubble property for a Billboard.js chart

Description

Bubble property for a Billboard.js chart

Usage

```
bb_bubble(bb, ...)
```

Arguments

bb A billboard htmlwidget object.
... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#.bubble>

Value

A billboard htmlwidget object.

Examples

```
billboarder() %>%  
  bb_scatterplot(  
    data = iris,  
    mapping = bbaes(Sepal.Length, Sepal.Width, group = Species, size = Petal.Width)  
  ) %>%  
  bb_bubble(maxR = 10)
```

```
billboarder() %>%  
  bb_scatterplot(  
    data = iris,  
    mapping = bbaes(Sepal.Length, Sepal.Width, group = Species, size = Petal.Width)  
  ) %>%  
  bb_bubble(maxR = JS("function(d) {return Math.sqrt(d.value.z * 20);}"))
```

bb_callbacks

Callbacks for billboard charts

Description

Callbacks for billboard charts

Usage

```
bb_callbacks(  
  bb,  
  onafterinit = NULL,  
  onbeforeinit = NULL,  
  oninit = NULL,  
  onout = NULL,  
  onover = NULL,  
  onrendered = NULL,  
  onresize = NULL,  
  onresized = NULL  
)
```

Arguments

bb	A billboard htmlwidget object.
onafterinit	Set a callback to execute after the chart is initialized.
onbeforeinit	Set a callback to execute before the chart is initialized.
oninit	Set a callback to execute when the chart is initialized.
onout	Set a callback to execute when mouse/touch leaves the chart.
onover	Set a callback to execute when mouse/touch enters the chart.
onrendered	Set a callback which is executed when the chart is rendered. Basically, this callback will be called in each time when the chart is redrawn.
onresize	Set a callback to execute when user resizes the screen.
onresized	Set a callback to execute when screen resize finished.

Value

A billboard htmlwidget object.

Note

Set JavaScript callbacks for various billboard events. See the [billboard options](#) reference for additional details on the signature of each callback.

bb_categories	<i>Set categories on X axis</i>
---------------	---------------------------------

Description

Set or modify x axis labels.

Usage

```
bb_categories(bb, categories)
```

Arguments

bb	A billboard htmlwidget object.
categories	A character vector to set names on a category axis.

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarder-shiny](#) to modify labels on axis, e.g. for barcharts.

Examples

```
# Simple line with month names as x labels
billboarder() %>%
  bb_linechart(data = round(rnorm(12))) %>%
  bb_categories(categories = month.name)
```

bb_color

Color property for a Billboard.js chart

Description

Color property for a Billboard.js chart

Usage

```
bb_color(bb, palette = NULL, ...)
```

Arguments

bb	A billboard htmlwidget object.
palette	A color palette to use with series added in the chart.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.color

Value

A billboard htmlwidget object.

Examples

```
library("RColorBrewer")

# Scatter
billboarder() %>%
  bb_scatterplot(data = iris, x = "Sepal.Length", y = "Sepal.Width", group = "Species") %>%
  bb_axis(x = list(tick = list(fit = FALSE))) %>%
  bb_point(r = 8) %>%
  bb_color(palette = brewer.pal(n = 3, name = "Reds"))

# Pie
stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer", "shinyWidgets", "visNetwork"),
  stars = c(9, 177, 43, 44, 169)
)
cols <- brewer.pal(n = 5, name = "Dark2")

billboarder() %>%
```



```
bb_piechart(data = stars) %>%
  bb_color(palette = brewer.pal(n = 5, name = "Reds"))
```

bb_colors_manual	<i>Set colors for each datas</i>
------------------	----------------------------------

Description

Set colors for each datas

Usage

```
bb_colors_manual(bb, ..., opacity = 1)
```

Arguments

bb	A billboard htmlwidget object.
...	A named list, where names correspond to the data, and values to color associate with it.
opacity	Color opacity (for area charts).

Value

A billboard htmlwidget object.

Examples

```
library("RColorBrewer")

# Scatter
billboarder() %>%
  bb_scatterplot(
    data = iris,
    x = "Sepal.Length",
    y = "Sepal.Width",
    group = "Species"
  ) %>%
  bb_axis(x = list(tick = list(fit = FALSE))) %>%
  bb_point(r = 8) %>%
  bb_colors_manual(
    setosa = "#440154",
    virginica = "#21908C",
    versicolor = "#FDE725"
  )

# Pie
stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer",
```

```
      "shinyWidgets", "visNetwork"),
    stars = c(9, 177, 43, 44, 169)
  )
cols <- brewer.pal(n = 5, name = "Dark2")

billboarder() %>%
  bb_piechart(data = stars) %>%
  bb_colors_manual(
    setNames(as.list(cols), stars$package) # this is a named list
  )
```

bb_data

Add data to Billboard chart

Description

Add data to Billboard chart

Usage

```
bb_data(bb, ...)
```

Arguments

bb A billboard htmlwidget object.
... Arguments defined in <https://naver.github.io/billboard.js/demo/>.

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarderProxy](#) in shiny application.

Examples

```
billboarder() %>%
  bb_barchart(data = table(mtcars$cyl)) %>%
  bb_data(names = list(Freq = "Number of cylinders"), labels = TRUE)
```

bb_densityplot *Helper for creating a density plot*

Description

Helper for creating a density plot

Usage

```
bb_densityplot(  
  bb,  
  data,  
  mapping = NULL,  
  stacked = FALSE,  
  stat = "density",  
  fill = FALSE,  
  ...  
)
```

Arguments

bb	A billboard htmlwidget object.
data	A data.frame or a vector, the first column will be used to calculate density if x is NULL.
mapping	Mapping of variables on the chart, see bbaes .
stacked	Logical, create a stacked density plot.
stat	Stat to compute : density or count.
fill	Produce a conditional density estimate, this option force stacked = TRUE.
...	Arguments passed to density .

Value

A billboard htmlwidget object.

See Also

[bb_histogram](#)

Examples

```
# With a vector  
billboarder() %>%  
  bb_densityplot(data = rnorm(1e4))  
  
data("diamonds", package = "ggplot2")
```

```

# density plot with one variable
billboarder() %>%
  bb_densityplot(data = diamonds, x = "carat")

# Same with mapping
billboarder() %>%
  bb_densityplot(diamonds, bbaes(carat))

# With a grouping variable
billboarder() %>%
  bb_densityplot(data = diamonds, x = "depth", group = "cut") %>%
  bb_x_axis(min = 55, max = 70)

# Same with mapping
billboarder() %>%
  bb_densityplot(diamonds, bbaes(depth, group = cut)) %>%
  bb_x_axis(min = 55, max = 70)

# a stacked density plot using count as statistic
bb <- billboarder() %>%
  bb_densityplot(diamonds, bbaes(depth, group = cut),
                stacked = TRUE, stat = "count") %>%
  bb_x_axis(min = 55, max = 70)
bb

# changing order
bb %>% bb_data(order = "asc")

```

bb_donut

Donut property for a Billboard.js chart

Description

Donut property for a Billboard.js chart

Usage

```
bb_donut(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.donut

Value

A billboard htmlwidget object.

Examples

```
billboarder() %>%
  bb_donutchart(data = table(mtcars$cyl)) %>%
  bb_donut(title = "Donut Title", width = 10)
```

bb_donutchart	<i>Helper for creating a donut chart</i>
---------------	--

Description

Helper for creating a donut chart

Usage

```
bb_donutchart(bb, data, mapping = NULL, ...)
```

Arguments

bb	A billboard htmlwidget object.
data	A data.frame.
mapping	Mapping of variables on the chart, see bbaes .
...	Arguments for slot donut, https://naver.github.io/billboard.js/release/latest/doc/Options.html#.donut .

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarderProxy](#) in shiny application.

Examples

```
## Not run:
stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer", "shinyWidgets", "visNetwork"),
  stars = c(9, 177, 43, 44, 169)
)

billboarder() %>%
  bb_donutchart(data = stars, title = "Stars")

## End(Not run)
```

 bb_export

Export a Billboard to PNG

Description

Export a Billboard to PNG

Usage

```
bb_export(bb, filename = NULL, download_label = "Export (.png)", ...)
```

Arguments

bb	A billboarder htmlwidget object or a billboarderProxy htmlwidget object.
filename	A string of the filename, excluding extension (will be ".png").
download_label	Label to appear on the link to download PNG.
...	Additional arguments (not used).

Value

A billboard htmlwidget object.

Note

This function has two uses:

- **in shiny:** you can export to PNG with an observeEvent by using [billboarderProxy](#).
- **in markdown and in shiny:** add a button to download chart as PNG.

Examples

```
# Add a button to download as PNG:

data("equilibre_mensuel")
billboarder() %>%
  bb_linechart(
    data = equilibre_mensuel,
    mapping = bbaes(date, solde),
    type = "spline"
  ) %>%
  bb_x_axis(
    tick = list(format = "%Y-%m", fit = FALSE)
  ) %>%
  bb_export(
    filename = "my-awesome-chart",
    download_label = "Click to download"
  )
```

```

# In shiny, you can use proxy :

if (interactive()) {
  library(shiny)
  library(billboarder)

  ui <- fluidPage(
    fluidRow(
      column(
        width = 8, offset = 2,
        tags$h1("Export billboard as PNG via Proxy"),
        billboarderOutput(outputId = "mybb"),
        actionButton(
          inputId = "export",
          label = "Export",
          icon = icon("download")
        )
      )
    )
  )
}

server <- function(input, output, session) {

  output$mybb <- renderBillboarder({
    data("prod_par_filiere")
    billboarder() %>%
      bb_barchart(
        data = prod_par_filiere[, c("annee", "prod_hydraulique")],
        color = "#102246"
      ) %>%
      bb_y_grid(show = TRUE)
  })

  observeEvent(input$export, {
    billboarderProxy(shinyId = "mybb") %>%
      bb_export(filename = "my-billboard-chart")
  })

}

shinyApp(ui, server)
}

```

bb_gauge

Gauge property for a Billboard.js chart

Description

Gauge property for a Billboard.js chart

Usage

```
bb_gauge(bb, ...)
```

Arguments

bb A billboard htmlwidget object.

... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#gauge>

Value

A billboard htmlwidget object.

Examples

```
billboarder() %>%
  bb_gaugechart(value = 50) %>%
  bb_gauge(min = 0, max = 200, units = "km/h", width = 10,
           label = list(format = htmlwidgets::JS("function(value) {return value;}")))
```

bb_gaugechart	<i>Helper for creating a gauge</i>
---------------	------------------------------------

Description

Helper for creating a gauge

Usage

```
bb_gaugechart(
  bb,
  value,
  name = "Value",
  color = NULL,
  steps = c(30, 60, 90, 100),
  steps_color = c("#FF0000", "#F97600", "#F6C600", "#60B044"),
  ...
)
```

Arguments

bb A billboard htmlwidget object.

value A single numeric value or a vector for stacked gauge.

name Name for the value, appear in tooltip, same length as ‘value’.

color Color for the gauge, if provided, ‘steps’ and ‘steps_color’ are ignored.

steps	Upper bound for changing colors
steps_color	Colors corresponding to steps
...	Arguments for slot gauge.

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarderProxy](#) in shiny application.

Examples

```
billboarder() %>%
  bb_gaugechart(value = 50)

# With some options
billboarder() %>%
  bb_gaugechart(
    value = 160,
    steps_color = rev(c("#FF0000", "#F97600", "#F6C600", "#60B044"))
  ) %>%
  bb_gauge(
    label = list(format = suffix("km/h")),
    min = 10, max = 200, width = 20
  )
```

bb_grid

Grid property for a Billboard.js chart

Description

Grid property for a Billboard.js chart

Usage

```
bb_grid(bb, ...)
```

```
bb_x_grid(bb, ...)
```

```
bb_y_grid(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.grid

Value

A billboard htmlwidget object.

Note

bb_x_grid and bb_y_grid are shortcut for modifying the x-axis and the y-axis respectively.

Examples

```
stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer", "shinyWidgets", "visNetwork"),
  stars = c(1, 176, 42, 40, 166)
)

billboarder() %>%
  bb_barchart(data = stars) %>%
  bb_y_grid(show = TRUE)

billboarder() %>%
  bb_barchart(data = stars) %>%
  bb_y_grid(lines = list(list(value = mean(stars$stars), text = "Horizontal line")))
```

bb_histogram

Helper for creating an histogram

Description

Helper for creating an histogram

Usage

```
bb_histogram(
  bb,
  data,
  mapping = NULL,
  stacked = FALSE,
  fill = FALSE,
  bins = 30,
  binwidth = NULL,
  ...
)
```

Arguments

bb A billboard htmlwidget object.

data A data.frame or a vector, the first column will be used to calculate density if x is NULL.

mapping	Mapping of variables on the chart, see bbaes .
stacked	Logical, create a stacked histogram.
fill	Logical, create a stacked percentage histogram.
bins	Number of bins. Overridden by binwidth. Defaults to 30.
binwidth	The width of the bins. See geom_histogram
...	Not used.

Value

A billboard htmlwidget object.

See Also

[bb_densityplot](#)

Examples

```
data("diamonds", package = "ggplot2")

# one variable
billboarder() %>%
  bb_histogram(data = diamonds, x = "price")

# with mapping
billboarder() %>%
  bb_histogram(diamonds, bbaes(price))

# equivalent to
billboarder() %>%
  bb_histogram(data = diamonds$price)

# prettier with 'binwidth'
# (but you need to know your data)
billboarder() %>%
  bb_histogram(data = diamonds, x = "price", binwidth = 500) %>%
  bb_colors_manual()

# with a grouping variable
billboarder() %>%
  bb_histogram(data = diamonds, x = "price",
              group = "cut", binwidth = 500)

# and with mapping
billboarder() %>%
  bb_histogram(diamonds, bbaes(price, group = cut),
              binwidth = 500)

# stacked histogram
billboarder() %>%
  bb_histogram(diamonds, bbaes(price, group = cut),
```

```

        stacked = TRUE, binwidth = 500)

# another example
dat <- data.frame(
  sample = c(rnorm(n = 500, mean = 1), rnorm(n = 500, mean = 2)),
  group = rep(c("A", "B"), each = 500)
)

billboarder() %>%
  bb_histogram(data = dat, x = "sample", binwidth = 0.25)

samples_mean <- tapply(dat$sample, dat$group, mean)
billboarder() %>%
  bb_histogram(data = dat, x = "sample", group = "group",
    binwidth = 0.25) %>%
  bb_x_grid(
    lines = list(
      list(value = unname(samples_mean['A']),
        text = "mean of sample A"),
      list(value = unname(samples_mean['B']),
        text = "mean of sample B")
    )
  )
)

```

bb_interaction

Interaction property for a Billboard.js chart

Description

Interaction property for a Billboard.js chart

Usage

```
bb_interaction(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#interaction

Value

A billboard htmlwidget object.

bb_labs *Quickly set title, axis labels and caption*

Description

Quickly set title, axis labels and caption

Usage

```
bb_labs(bb, title = NULL, x = NULL, y = NULL, caption = NULL, ...)
```

Arguments

bb	A billboard htmlwidget object.
title	Text for the chart title, use \n to make a new line.
x	Text for x axis title.
y	Text for y axis title.
caption	Text for the caption displayed in the bottom-right of the chart.
...	Not used.

Value

A billboard htmlwidget object.

Note

caption is not part of the billboard.js library, it is added by the billboardr package.

Examples

```
data("prod_par_filiere")

billboarder() %>%
  bb_barchart(
    data = prod_par_filiere[, c("annee", "prod_hydraulique")],
    color = "#102246"
  ) %>%
  bb_legend(show = FALSE) %>%
  bb_labs(
    title = "French hydraulic production",
    y = "production (in terawatt-hours)",
    caption = "Data source: RTE (https://opendata.reseaux-energies.fr/)",
    caption_href = "https://opendata.reseaux-energies.fr/"
  )
```

`bb_legend`*Add legend parameters*

Description

Add legend parameters

Usage

```
bb_legend(bb, ...)
```

Arguments

<code>bb</code>	A billboard htmlwidget object.
<code>...</code>	Arguments defined in https://naver.github.io/billboard.js/release/latest/doc/Options.html#.legend .

Value

A billboard htmlwidget object.

Examples

```
library("billboarder")

stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer", "shinyWidgets", "visNetwork"),
  stars = c(1, 176, 42, 40, 166)
)

# Hide legend
billboarder() %>%
  bb_barchart(data = stars) %>%
  bb_legend(show = FALSE)

# Right legend
billboarder() %>%
  bb_piechart(data = stars) %>%
  bb_legend(position = "right")

# Inset legend
billboarder() %>%
  bb_scatterplot(data = iris, x = "Sepal.Length", y = "Sepal.Width", group = "Species") %>%
  bb_axis(x = list(tick = list(fit = FALSE))) %>%
  bb_legend(position = "inset", inset = list(anchor = "top-right"))
```

bb_line	<i>Line property for a Billboard.js chart</i>
---------	---

Description

Line property for a Billboard.js chart

Usage

```
bb_line(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.line

Value

A billboard htmlwidget object.

Examples

```
# Set if null data point will be connected or not.
b <- billboarder() %>%
  bb_linechart(data = c(1, 2, NA, 4, 5))
b
b %>% bb_line(connectNull = TRUE)
```

bb_linechart	<i>Helper for creating a line chart</i>
--------------	---

Description

Helper for creating a line chart

Usage

```
bb_linechart(
  bb,
  data,
  mapping = NULL,
  type = "line",
  show_point = FALSE,
  dasharray = NULL,
```

```

    width = NULL,
    ...
  )

```

Arguments

bb	A billboard htmlwidget object.
data	A data.frame or a vector.
mapping	Mapping of variables on the chart, see bbaes .
type	Type of chart: "line", "spline", "step", "area", "area-spline", "area-step", "area-line-range", "area-spline-range".
show_point	Whether to show each point in line.
dasharray	Pattern of dashes and gaps used to paint the outline of the line, see https://developer.mozilla.org/en-US/docs/Web/SVG/Attribute/stroke-dasharray for specifications.
width	Width of the stroke to be applied to the line, see https://developer.mozilla.org/en-US/docs/Web/SVG/Attribute/stroke-width for specifications.
...	Not used.

Value

A billboard htmlwidget object.

Note

Types area-line-range and area-spline-range don't work in RStudio viewer, open chart in a browser. This function can be used with [billboarderProxy](#) in shiny application.

Examples

```

## Different types
x <- round(rnorm(20), 2)

billboarder() %>%
  bb_linechart(data = x)

billboarder() %>%
  bb_linechart(data = x, type = "spline")

billboarder() %>%
  bb_linechart(data = x, type = "area")

billboarder() %>%
  bb_linechart(data = x, type = "area-spline")

## Timeserie with date (Date)
data("economics", package = "ggplot2")

```



```

billboarder() %>%
  bb_linechart(data = economics[, c("date", "psavert")]) %>%
  bb_x_axis(tick = list(format = "%Y-%m", fit = FALSE)) %>%
  bb_y_axis(tick = list(format = suffix("%")),
            label = list(text = "Personal savings rate")) %>%
  bb_legend(show = FALSE) %>%
  bb_x_grid(show = TRUE) %>%
  bb_y_grid(show = TRUE) %>%
  bb_subchart(show = TRUE)

# With multiple lines :

data("economics_long", package = "ggplot2")

billboarder() %>%
  bb_linechart(economics_long, bbaes(date, value, variable)) %>%
  bb_data(hide = "pop") %>%
  bb_x_axis(tick = list(format = "%Y-%m", fit = FALSE))

## Timeserie with datetime (POSIXct)
data("cdc_prod_filiere")

billboarder() %>%
  bb_linechart(data = cdc_prod_filiere[, c("date_heure", "prod_eolien")])

# or with mapping :
billboarder() %>%
  bb_linechart(cdc_prod_filiere, bbaes(date_heure, prod_bioenergies))

### Other type for x-axis

## character/factor on x-axis
AirPassengers1960 <- data.frame(
  month = month.name,
  AirPassengers = tail(AirPassengers, 12)
)
# you have to specify that x-axis is of type 'category'
# and that column 'month' must be used for x-axis values
billboarder() %>%
  bb_linechart(data = AirPassengers1960, x = "month") %>%
  bb_x_axis(type = "category")

## numeric on x-axis
lynx.df <- data.frame(
  year = time(lynx),
  lynx = lynx
)

```

```

# just specify which variable must be use n the x-axis
billboarder() %>%
  bb_linechart(data = lynx.df, x = "year")

### Area range charts

# Generate data
dat <- data.frame(
  date = seq.Date(Sys.Date(), length.out = 20, by = "day"),
  y1 = round(rnorm(20, 100, 15)),
  y2 = round(rnorm(20, 100, 15))
)
dat$ymin1 <- dat$y1 - 5
dat$ymax1 <- dat$y1 + 5

dat$ymin2 <- dat$y2 - sample(3:15, 20, TRUE)
dat$ymax2 <- dat$y2 + sample(3:15, 20, TRUE)

# Make chart : use ymin & ymax aes for range
billboarder(data = dat) %>%
  bb_linechart(
    mapping = bbaes(x = date, y = y1, ymin = ymin1, ymax = ymax1),
    type = "area-line-range"
  ) %>%
  bb_linechart(
    mapping = bbaes(x = date, y = y2, ymin = ymin2, ymax = ymax2),
    type = "area-spline-range"
  ) %>%
  bb_y_axis(min = 50)

```

bb_load

Load data to the chart with proxy

Description

Load data to the chart with proxy

Usage

```
bb_load(proxy, data = NULL, unload = NULL, ...)
```

Arguments

proxy	A billboardProxy htmlwidget object.
data	A data.frame with updated data.
unload	Ids (names) to data to unload.
...	Arguments passed to method.

Value

A billboardProxy htmlwidget object.

 bb_lollipop

Helper for creating a lollipop chart

Description

Helper for creating a lollipop chart

Usage

```
bb_lollipop(
  bb,
  data,
  mapping = NULL,
  rotated = FALSE,
  point_color = "#112446",
  point_size = 8,
  line_color = "#000",
  ...
)
```

Arguments

bb	A billboard htmlwidget object.
data	A data.frame, the first column will be used for x axis unless argument x is specified, the second one will be use as y values. If not a data.frame, an object coercible to data.frame.
mapping	Mapping of variables on the chart, see bbaes .
rotated	Switch x and y axis position.
point_color	Color of the lollipop.
point_size	Size of the lollipop.
line_color	Color of the lines between the axis and the lollipop.
...	Not used.

Value

A billboard htmlwidget object.

Examples

```

# From wikipedia
sw <- data.frame(
  film = c("The Force Awakens", "The Phantom Menace",
           "Revenge of the Sith", "A New Hope",
           "Attack of the Clones", "The Empire Strikes Back",
           "Return of the Jedi"
  ),
  worldwide_gross = c(2068178225, 1027044677, 848754768,
                     775398007, 649398328, 538375067,
                     475106177)
)

# Simple example
billboarder() %>%
  bb_lollipop(data = sw)

# Fancy example
billboarder() %>%
  bb_lollipop(data = sw, rotated = TRUE)%>%
  bb_y_grid(show = TRUE) %>%
  bb_y_axis(tick = list(
    values = c(0, 5e+08, 1e+09, 1.5e+09, 2e+09),
    outer = FALSE,
    format = htmlwidgets::JS("d3.formatPrefix('$,.0', 1e6)")
  )) %>%
  bb_x_axis(tick = list(centered = TRUE)) %>%
  bb_labs(
    title = "Star Wars - Total Lifetime Grosses",
    caption = "Data source : wikipedia"
  )

# With mapping
billboarder(data = sw) %>%
  bb_lollipop(mapping = bbaes(x = film, y = worldwide_gross))

```

bb_padding

The padding of the chart element.

Description

The padding of the chart element.

Usage

```
bb_padding(bb, ...)
```

Arguments

bb	A billboarder htmlwidget object or a billboarderProxy htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.padding for possible options.

Value

A billboard htmlwidget object.

bb_pie	<i>Pie property for a Billboard.js chart</i>
--------	--

Description

Pie property for a Billboard.js chart

Usage

```
bb_pie(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.pie

Value

A billboard htmlwidget object.

Examples

```
billboarder() %>%
  bb_piechart(data = table(mtcars$cyl)) %>%
  bb_pie(label = list(
    ratio = 0.5,
    format = htmlwidgets::JS("function(value) {return d3.format('$')(value);}")
  ),
  expand = FALSE)
```

bb_piechart	<i>Helper for creating a pie chart</i>
-------------	--

Description

Helper for creating a pie chart

Usage

```
bb_piechart(bb, data, mapping = NULL, ...)
```

Arguments

bb	A billboard htmlwidget object.
data	A data.frame, first column should contain labels, second column values associated, except if mapping is provided.
mapping	Mapping of variables on the chart, see bbaes .
...	Arguments for slot pie, https://naver.github.io/billboard.js/release/latest/doc/Options.html#pie .

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarderProxy](#) in shiny application.

Examples

```
stars <- data.frame(
  package = c("billboarder", "ggiraph", "officer", "shinyWidgets", "visNetwork"),
  stars = c(9, 177, 43, 44, 169)
)

# Default
billboarder() %>%
  bb_piechart(data = stars)

# Explicit mapping
billboarder() %>%
  bb_piechart(data = stars, bbaes(package, stars))

# Other way to specify mapping
billboarder(data = stars) %>%
  bb_aes(package, stars) %>%
  bb_piechart()
```

bb_point	<i>Point property for a Billboard.js chart</i>
----------	--

Description

Point property for a Billboard.js chart

Usage

```
bb_point(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.point

Value

A billboard htmlwidget object.

Examples

```
# Set point size
billboarder() %>%
  bb_scatterplot(data = iris, x = "Sepal.Length", y = "Sepal.Width", group = "Species") %>%
  bb_axis(x = list(tick = list(fit = FALSE))) %>%
  bb_point(r = 10)
```

bb_proxy_axis_labels	<i>Update axis labels with proxy</i>
----------------------	--------------------------------------

Description

Update axis labels with proxy

Usage

```
bb_proxy_axis_labels(proxy, x = NULL, y = NULL)
```

Arguments

proxy	A billboardProxy htmlwidget object.
x	X axis label.
y	Y axis label.

Value

A billboardProxy htmlwidget object.

bb_proxy_data_colors *Change colors with proxy*

Description

Change colors with proxy

Usage

```
bb_proxy_data_colors(proxy, names = NULL, colors = NULL)
```

Arguments

proxy	A billboardProxy htmlwidget object.
names	Names of series
colors	New colors, in same order that names.

Value

A billboardProxy htmlwidget object.

Examples

```
if (interactive()) {

  library(shiny)
  library(billboarder)

  ui <- fluidPage(
    tags$h2("Update colors"),
    fluidRow(
      column(
        width = 3,
        selectizeInput(
          inputId = "col_eol",
          label = "Color for 'prod_eolien':",
          choices = c("#66C2A5", "#FC8D62",
                     "#8DA0CB", "#E78AC3",
                     "#A6D854", "#FFD92F",
                     "#E5C494", "#B3B3B3")
        ),
        selectizeInput(
          inputId = "col_sol",
          label = "Color for 'prod_solaire':",
          choices = c("#66C2A5", "#FC8D62",
```



```

        "#8DA0CB", "#E78AC3",
        "#A6D854", "#FFD92F",
        "#E5C494", "#B3B3B3")
    )
  ),
  column(
    width = 9,
    billboardOutput(outputId = "my_bb")
  )
)
)

server <- function(input, output, session) {

  output$my_bb <- renderBillboarder({
    data(prod_par_filiere)
    billboarder() %>%
      bb_barchart(
        data = prod_par_filiere[, c(1, 6, 8)]
      )
  })

  observe({
    billboardProxy(shinyId = "my_bb") %>%
      bb_proxy_data_colors(
        names = c("prod_eolien", "prod_solaire"),
        colors = c(input$col_eol, input$col_sol)
      )
  })

}

shinyApp(ui, server)

}

```

bb_proxy_data_names *Change names of the data with proxy*

Description

Change names of the data with proxy

Usage

```
bb_proxy_data_names(proxy, old = NULL, new = NULL)
```

Arguments

proxy	A billboardProxy htmlwidget object.
old	Old names
new	New names

Value

A billboardProxy htmlwidget object.

Examples

```

if (interactive()) {

  library(shiny)
  library(billboarder)

  ui <- fluidPage(
    tags$h2("Update axis title & data name (tooltip & legend)",
    billboarderOutput(outputId = "my_bb"),
    textInput(
      inputId = "new_name",
      label = "New name :",
      value = "this is a new name",
      width = "100%"
    ),
    actionButton(
      inputId = "update",
      label = "Update chart",
      width = "100%"
    )
  )

  server <- function(input, output, session) {

    output$my_bb <- renderBillboarder({
      dat <- sample(letters[1:5], 100, TRUE)
      billboarder() %>%
        bb_barchart(data = table(dat)) %>%
        bb_y_axis(label = list(text = "Freq"))
    })

    observeEvent(input$update, {
      dat <- sample(letters[1:5], 100, TRUE)
      billboarderProxy(shinyId = "my_bb") %>%
        bb_proxy_axis_labels(y = input$new_name) %>%
        bb_proxy_data_names(old = "Freq",
                           new = input$new_name) %>%
        bb_barchart(data = table(dat))
    }, ignoreInit = TRUE)
  }
}

```

```
shinyApp(ui, server)
}
```

bb_proxy_flow

Update chart flow with proxy

Description

Update chart flow with proxy

Usage

```
bb_proxy_flow(proxy, ...)
```

Arguments

proxy	A billboardProxy htmlwidget object.
...	Arguments passed to the flow API, see https://naver.github.io/billboard.js/release/latest/doc/Chart.html#flow .

Value

A billboardProxy htmlwidget object.

Examples

```
if (interactive()) {
  library(shiny)
  library(billboarder)

  ui <- fluidPage(
    tags$h3("Proxy flow"),
    actionButton(
      inputId = "next_data",
      label = "Add data",
      icon = icon("arrow-right")
    ),
    billboarderOutput(outputId = "chart1"),

    tags$h4("Real time chart"),
    billboarderOutput(outputId = "chart2")
  )

  server <- function(input, output, session) {

    time_data <- reactiveValues(df = data.frame(
```

```

    x = Sys.Date() + 1:20,
    y = round(rnorm(20) * 10)
  })

  output$chart1 <- renderBillboarder({
    billboarder() %>%
      bb_linechart(data = isolate(time_data$df))
  })

  observeEvent(input$next_data, {
    time_data$df$x <- time_data$df$x + 21
    time_data$df$y <- round(rnorm(20) * 10)
  })

  observe({
    billboarderProxy("chart1") %>%
      bb_proxy_flow(json = as.list(time_data$df), duration = 1500)
  })

  output$chart2 <- renderBillboarder({
    df <- data.frame(
      x = Sys.time() - 1:20 * 2,
      y = round(rnorm(20) * 10)
    )
    billboarder() %>%
      bb_linechart(data = df) %>%
      bb_x_axis(tick = list(format = "%H:%M", fit = FALSE))
  })

  observe({
    invalidateLater(2000)
    billboarderProxy("chart2") %>%
      bb_proxy_flow(json = list(
        x = list(format(Sys.time())),
        y = list(round(rnorm(1) * 10))
      ), data = list(x = "x"))
  })
}

shinyApp(ui, server)
}

```

bb_proxy_focus

Highlights specified targets and fade out the others.

Description

Highlights specified targets and fade out the others.

Usage

```
bb_proxy_focus(proxy, ids = NULL)
```

```
bb_proxy_defocus(proxy, ids = NULL)
```

Arguments

proxy A billboardProxy htmlwidget object.
ids Data ids (names) to be highlighted, if NULL all datas will be highlighted.

Value

A billboardProxy htmlwidget object.

Note

bb_defocus is the opposite of bb_focus

Examples

```
if (interactive()) {
  library("shiny")
  library("billboarder")

  ui <- fluidPage(
    tags$h1("Proxy method to highlight data"),
    checkboxGroupInput(
      inputId = "focus",
      label = "Focus",
      choices = c("setosa", "versicolor", "virginica"),
      inline = TRUE
    ),
    billboarderOutput(outputId = "bb")
  )

  server <- function(input, output, session) {

    output$bb <- renderBillboarder({
      billboarder() %>%
        bb_scatter(
          data = iris,
          x = "Sepal.Length",
          y = "Sepal.Width",
          group = "Species"
        ) %>%
        bb_axis(x = list(tick = list(fit = FALSE))) %>%
        bb_point(r = 8)
    })

    observeEvent(input$focus, {
      billboarderProxy("bb") %>%
```

```

      bb_proxy_focus(input$focus)
    }, ignoreNULL = FALSE)
  }

  shinyApp(ui = ui, server = server)
}

```

bb_proxy_groups	<i>Update chart groups with proxy</i>
-----------------	---------------------------------------

Description

Update chart groups with proxy

Usage

```
bb_proxy_groups(proxy, ...)
```

Arguments

proxy	A billboardProxy htmlwidget object.
...	Vector(s) with id of the series, e.g. the name of variables.

Value

A billboardProxy htmlwidget object.

bb_proxy_hide	<i>Hide method with proxy</i>
---------------	-------------------------------

Description

Hide method with proxy

Usage

```
bb_proxy_hide(proxy, targetIdsValue, options = NULL)
```

Arguments

proxy	A billboardProxy htmlwidget object.
targetIdsValue	Name of series to hide.
options	Additional options.

Value

A billboardProxy htmlwidget object.

See Also

[bb_proxy_show](#)

bb_proxy_legend	<i>Show or hide legend with proxy</i>
-----------------	---------------------------------------

Description

Show or hide legend with proxy

Usage

```
bb_proxy_legend(proxy, what = c("show", "hide"), targetIds = NULL)
```

Arguments

proxy	A billboardProxy htmlwidget object.
what	show or hide the legend.
targetIds	Series ids to show/hide, if NULL show/hide all legend.

Value

A billboardProxy htmlwidget object.

Examples

```
if (interactive()) {
  library("shiny")

  data("prod_par_filiere")

  ui <- fluidPage(
    tags$h2("Show or hide legend with Proxy"),
    fluidRow(
      column(
        width = 3,
        checkboxInput(
          inputId = "show_legend",
          label = "Show legend",
          value = TRUE
        ),
        checkboxGroupInput(
          inputId = "item_show",
          label = "Item to show in legend",
```

```

        choices = c("Hydraulic" = "prod_hydraulique",
                    "Wind" = "prod_eolien",
                    "Solar" = "prod_solaire"),
        selected = c("prod_hydraulique", "prod_eolien", "prod_solaire")
    )
  ),
  column(
    width = 9,
    billboardOutput(outputId = "mybb")
  )
)
)

server <- function(input, output, session) {

  output$mybb <- renderBillboarder({
    billboarder() %>%
      bb_barchart(
        data = prod_par_filiere[, c(
          "annee", "prod_hydraulique",
          "prod_eolien", "prod_solaire"
        )],
        stacked = TRUE
      ) %>%
      bb_data(
        names = list(prod_hydraulique = "Hydraulic",
                    prod_eolien = "Wind",
                    prod_solaire = "Solar"),
        labels = TRUE
      ) %>%
      bb_colors_manual(
        "prod_eolien" = "#41AB5D",
        "prod_hydraulique" = "#4292C6",
        "prod_solaire" = "#FEB24C"
      ) %>%
      bb_y_grid(show = TRUE) %>%
      bb_y_axis(
        tick = list(format = suffix("TWh")),
        label = list(text = "production (in terawatt-hours)",
                    position = "outer-top")
      ) %>%
      bb_legend(position = "right") %>%
      bb_labs(
        title = "Renewable energy production",
        caption = "Data source: RTE (https://opendata.rte-france.com)"
      )
  })

  observe({
    if (input$show_legend) {
      billboarderProxy("mybb") %>%
        bb_proxy_legend(what = "show")
    } else {

```



```

        billboardProxy("mybb") %>%
          bb_proxy_legend(what = "hide")
      }
    })

    observe({
      lapply(
        X = c("prod_hydraulique", "prod_eolien", "prod_solaire"),
        FUN = function(x) {
          if (x %in% input$item_show) {
            billboardProxy("mybb") %>%
              bb_proxy_legend(what = "show", targetIds = x)
          } else {
            billboardProxy("mybb") %>%
              bb_proxy_legend(what = "hide", targetIds = x)
          }
        }
      )
    })
  }

  shinyApp(ui = ui, server = server)
}

```

bb_proxy_show

Show method with proxy

Description

Show method with proxy

Usage

```
bb_proxy_show(proxy, targetIdsValue, options = NULL)
```

Arguments

proxy A billboardProxy htmlwidget object.
targetIdsValue Name of series to show.
options Additional options.

Value

A billboardProxy htmlwidget object.

See Also

[bb_proxy_hide](#)

bb_proxy_tooltip *Show or hide tooltip with proxy*

Description

Show or hide tooltip with proxy

Usage

```
bb_proxy_tooltip(proxy, what = c("show", "hide"), x = NULL, index = NULL, ...)
```

Arguments

proxy	A billboardProxy htmlwidget object.
what	show or hide the legend.
x	x value on which the tooltip must appear.
index	Index on the x-axis on which the tooltip must appear.
...	Additional arguments passed to method.

Value

A billboardProxy htmlwidget object.

bb_proxy_transform *Update chart type with proxy*

Description

Update chart type with proxy

Usage

```
bb_proxy_transform(proxy, type, targetIds = NULL)
```

Arguments

proxy	A billboardProxy htmlwidget object.
type	Specify the type to be transformed.
targetIds	Specify targets to be transformed. If not given, all targets will be the candidate.

Value

A billboardProxy htmlwidget object.

bb_proxy_xs	<i>Update x values with proxy</i>
-------------	-----------------------------------

Description

Update x values with proxy

Usage

```
bb_proxy_xs(proxy, xs)
```

Arguments

proxy	A billboardProxy htmlwidget object.
xs	Named list of vector(s) used for x values.

Value

A billboardProxy htmlwidget object.

bb_radar	<i>Radar property for a Billboard.js chart</i>
----------	--

Description

Radar property for a Billboard.js chart

Usage

```
bb_radar(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.radar

Value

A billboard htmlwidget object.

Examples

```

library("billboarder")
data("avengers")

# number of levels
billboarder() %>%
  bb_radarchart(
    data = avengers,
    mapping = bbaes(x = axis, y = value, group = group)
  ) %>%
  bb_radar(level = list(depth = 4))

# hide levels
billboarder() %>%
  bb_radarchart(
    data = avengers,
    mapping = bbaes(x = axis, y = value, group = group)
  ) %>%
  bb_radar(level = list(show = FALSE))

# max value on axis
billboarder() %>%
  bb_radarchart(
    data = avengers,
    mapping = bbaes(x = axis, y = value, group = group)
  ) %>%
  bb_radar(axis = list(max = 10))

```

bb_radarchart *Helper for creating a radar chart*

Description

Helper for creating a radar chart

Usage

```
bb_radarchart(bb, data, mapping = NULL, ...)
```

Arguments

bb	A billboard htmlwidget object.
data	A <code>data.frame</code> , the first column will be used for x axis unless specified otherwise in mapping. If not a <code>data.frame</code> , an object coercible to <code>data.frame</code> .
mapping	Mapping of variables on the chart, see bbaes .
...	Arguments passed to bb_radar .

Value

A billboard htmlwidget object.

Examples

```
library("billboarder")

# data about Avengers
data("avengers_wide")

# if not specified, first column is used as x-axis,
# all others are used on y-axis
billboarder() %>%
  bb_radarchart(data = avengers_wide)

# specify explicitly which column to use with mapping
billboarder() %>%
  bb_radarchart(
    data = avengers_wide,
    mapping = bbaes(x = axis, y = `Captain America`)
  )

# with data in "long" format you can use "group" aesthetics
data("avengers")
billboarder() %>%
  bb_radarchart(
    data = avengers,
    mapping = bbaes(x = axis, y = value, group = group)
  )
```

bb_regions

Regions property for a Billboard.js chart

Description

Add a shading effect to the background of the chart, to highlight a period for example.

Usage

```
bb_regions(bb, ...)
```

Arguments

bb A billboard htmlwidget object.

... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#.regions>

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarderProxy](#) in shiny application.

See Also

[bb_add_style](#)

Examples

```
#' With a categorical X-axis
dat <- data.frame(
  month = month.abb,
  AirPassengers = tail(AirPassengers, 12)
)
# Highlight Jun/Jul/Aug
billboarder() %>%
  bb_linechart(data = dat, x = "month") %>%
  bb_x_axis(type = "category") %>%
  bb_regions(
    list(start = 4.5, end = 7.5) #' jan = 0
  )

# With a barchart
billboarder() %>%
  bb_barchart(data = dat) %>%
  bb_regions(
    list(start = 1.5, end = 2.5, class = "custom"),
    list(start = 8, end = 10, class = "foo")
  ) %>%
  bb_add_style(region = list(custom = "fill: red;", foo = "fill: #'009246;"))

# With Date X-axis
library("stats")
dat <- data.frame(
  date = seq.Date(from = Sys.Date(), by = "day", length.out = 365),
  var = density(rexp(n = 1000), n = 365)$y
)

billboarder() %>%
  bb_linechart(data = dat) %>%
  bb_x_axis(tick = list(fit = FALSE)) %>%
  bb_y_axis(min = 0, padding = 0) %>%
  bb_regions(
    list(start = format(Sys.Date() + 30), end = format(Sys.Date() + 120))
  )
```

```
# With POSIXct X-axis
dat <- data.frame(
  time = seq.POSIXt(from = Sys.time(), by = "min", length.out = 60),
  var = round(sort(rnorm(60)), 2)
)

billboarder() %>%
  bb_linechart(data = dat) %>%
  bb_x_axis(tick = list(format = "%H:%M", fit = FALSE)) %>%
  bb_regions(
    list(start = format(dat$time[15]),
         end = format(dat$time[30]))
  )
```

bb_render

Render property for a Billboard.js chart

Description

Render property for a Billboard.js chart

Usage

```
bb_render(bb, ...)
```

Arguments

bb	A billboarder htmlwidget object or a billboarderProxy htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.render for possible options.

Value

A billboard htmlwidget object.

bb_scatterplot *Helper for creating a scatter chart*

Description

Helper for creating a scatter chart

Usage

```
bb_scatterplot(bb, data, mapping = NULL, ..., point_opacity = NULL)
```

Arguments

bb	A billboard htmlwidget object.
data	A data.frame
mapping	Mapping of variables on the chart, see bbaes .
...	Alternative mapping, you can specify x = "Sepal.Length" for example.
point_opacity	Opacity for points, value between [0,1].

Value

A billboard htmlwidget object.

Note

This function can be used with [billboarderProxy](#) in shiny application.

Examples

```
# Use first and second variable by default
billboarder() %>%
  bb_scatterplot(data = iris)

# Explicit mapping
billboarder() %>%
  bb_scatterplot(
    data = iris,
    mapping = bbaes(Petal.Length, Petal.Width)
  ) %>%
  bb_x_axis(tick = list(fit = FALSE))

# Grouping variable
billboarder() %>%
  bb_scatterplot(
    data = iris,
    mapping = bbaes(Sepal.Length, Sepal.Width, group = Species)
```



```
)  
  
# Size variable  
billboarder() %>%  
  bb_scatterplot(  
    data = iris,  
    mapping = bbaes(  
      Sepal.Length, Sepal.Width,  
      group = Species, size = Petal.Width  
    )  
  ) %>%  
  bb_x_axis(tick = list(fit = FALSE))
```

bb_spline*Spline property for a Billboard.js chart*

Description

Spline property for a Billboard.js chart

Usage

```
bb_spline(bb, ...)
```

Arguments

bb A billboard htmlwidget object.
... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#.spline>

Value

A billboard htmlwidget object.

bb_subchart*Subchart property for a Billboard.js chart*

Description

Create a subchart allowing to zoom and navigate on the chart.

Usage

```
bb_subchart(bb, ...)
```

Arguments

bb A billboard htmlwidget object.
... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#.subchart>

Value

A billboard htmlwidget object.

Examples

```
data("equilibre_mensuel")  
  
billboarder() %>%  
  bb_linechart(data = equilibre_mensuel[, c("date", "production")], type = "spline") %>%  
  bb_subchart(show = TRUE)
```

bb_svg

SVG property for a Billboard.js chart

Description

SVG property for a Billboard.js chart

Usage

```
bb_svg(bb, ...)
```

Arguments

bb A billboard htmlwidget object.
... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#.svg>

Value

A billboard htmlwidget object.

bb_title	<i>Add title to Billboard.js chart</i>
----------	--

Description

Add title to Billboard.js chart

Usage

```
bb_title(bb, text = NULL, padding = NULL, position = "top-center", ...)
```

Arguments

bb	A billboard htmlwidget object.
text	The chart title.
padding	A named list with top, right, bottom, left values.
position	A string specifying the position of the title.
...	Additional arguments.

Value

A billboard htmlwidget object.

See Also

[bb_labs](#)

Examples

```
billboarder() %>%  
  bb_barchart(data = table(sample(letters, 100, TRUE))) %>%  
  bb_title(text = "Random letters", position = "center")
```

bb_tooltip	<i>Tooltip property for a Billboard.js chart</i>
------------	--

Description

Tooltip property for a Billboard.js chart

Usage

```
bb_tooltip(bb, ...)
```

Arguments

bb A billboard htmlwidget object.
 ... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#.tooltip>

Value

A billboard htmlwidget object.

Examples

```
# Format tooltip
billboarder() %>%
  bb_scatterplot(data = iris, x = "Sepal.Length", y = "Sepal.Width", group = "Species") %>%
  bb_tooltip(
    format = list(
      # skip the title in tooltip
      title = htmlwidgets::JS("function() {return undefined;}"),
      name = htmlwidgets::JS("function(name, ratio, id, index) {return '';}"),
      value = htmlwidgets::JS("function(value, ratio, id, index) {return id;}")
    )
  )
```

 bb_transition

Transition property for a Billboard.js chart

Description

Transition property for a Billboard.js chart

Usage

```
bb_transition(bb, ...)
```

Arguments

bb A billboard htmlwidget object.
 ... See <https://naver.github.io/billboard.js/release/latest/doc/Options.html#.transition>

Value

A billboard htmlwidget object.

bb_treemap	<i>Treemap property for a Billboard.js chart</i>
------------	--

Description

Treemap property for a Billboard.js chart

Usage

```
bb_treemap(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.treemap

Value

A billboard htmlwidget object.

Examples

```
library("billboarder")
data("mpg", package = "ggplot2")

billboarder() %>%
  bb_treemapchart(mpg[, 1]) %>%
  bb_treemap(label = list(show = TRUE, threshold = 0.03)) %>%
  bb_data(
    labels = list(colors = "#FFF")
  )
```

bb_treemapchart	<i>Helper for creating a treemap chart</i>
-----------------	--

Description

Helper for creating a treemap chart

Usage

```
bb_treemapchart(bb, data, mapping = NULL, ...)
```

Arguments

bb	A billboard htmlwidget object.
data	A data.frame, the first column will be used for x axis unless specified otherwise in mapping. If not a data.frame, an object coercible to data.frame.
mapping	Mapping of variables on the chart, see bbaes .
...	Arguments passed to bb_treemap .

Value

A billboard htmlwidget object.

Examples

```
library("billboarder")
data("mpg", package = "ggplot2")

billboarder() %>%
  bb_treemapchart(mpg[, 1])

billboarder() %>%
  bb_treemapchart(
    data = mpg,
    mapping = aes(x = manufacturer),
    label = list(show = TRUE, threshold = 0.3)
  ) %>%
  bb_data(
    labels = list(colors = "#FFF")
  )
```

bb_unload

Unload data to the chart with proxy

Description

Unload data to the chart with proxy

Usage

```
bb_unload(proxy, ids = NULL)
```

Arguments

proxy	A billboardProxy htmlwidget object.
ids	Data ids to unload.

Value

A billboardProxy htmlwidget object.

bb_zoom	<i>Zoom property for a Billboard.js chart</i>
---------	---

Description

Zoom property for a Billboard.js chart

Usage

```
bb_zoom(bb, ...)
```

Arguments

bb	A billboard htmlwidget object.
...	See https://naver.github.io/billboard.js/release/latest/doc/Options.html#.zoom

Value

A billboard htmlwidget object.

Examples

```
# data
data("equilibre_mensuel")

# line chart
billboarder() %>%
  bb_linechart(
    data = equilibre_mensuel[, c("date", "consommation", "production")],
    type = "spline"
  ) %>%
  bb_x_axis(tick = list(format = "%Y-%m", fit = FALSE)) %>%
  bb_zoom(enabled = TRUE)
```

billboard-aes	<i>Map variables on the chart</i>
---------------	-----------------------------------

Description

Map variables on the chart

Usage

```
bb_aes(bb, ...)  
bb_aes_string(bb, ...)  
bbaes(...)  
bbaes_string(...)
```

Arguments

<code>bb</code>	A billboard <code>htmlwidget</code> object.
<code>...</code>	Mapping parameters, such as <code>x</code> for x-axis, <code>y</code> for y-axis, <code>group</code> for grouping variable.

Value

A billboard `htmlwidget` object.

Note

`bb_aes` is intended to use in a "piping" way. `bbaes` is the equivalent to use inside a helper function such as `bb_barchart`, `bb_scatterplot`...

Examples

```
## Not run:  
dat <- as.data.frame(table(sample(letters[1:5], 100, TRUE)))  
  
billboarder(data = dat) %>%  
  bb_aes(x = Var1, y = Freq) %>%  
  bb_barchart()  
  
tab <- table(sample(letters[1:5], 100, TRUE), sample(LETTERS[1:5], 100, TRUE))  
dat_group <- as.data.frame(tab)  
  
billboarder(data = dat_group) %>%  
  bb_aes(x = Var1, y = Freq, group = "Var2") %>%  
  bb_barchart()  
  
## End(Not run)
```

billboard-theme	<i>Set theme and default colors for Billboard charts</i>
-----------------	--

Description

Set theme and default colors for Billboard charts

Usage

```
set_theme(name = c("billboard", "insight", "graph", "datalab", "modern"))
set_color_palette(colors)
```

Arguments

name	Name of the theme, possible values are : "billboard", "insight", "graph", "datalab", "modern".
colors	Vector of colors to use as default.

Note

You can only use one theme and palette at a time (in Shiny applications or Markdown documents).

Examples

```
library("billboarder")
set_theme("insight")

data("prod_par_filiere")
billboarder() %>%
  bb_barchart(
    data = prod_par_filiere[, c("annee", "prod_hydraulique", "prod_eolien", "prod_solaire")]
  ) %>%
  bb_data(
    names = list(prod_hydraulique = "Hydraulic", prod_eolien = "Wind", prod_solaire = "Solar")
  ) %>%
  bb_y_grid(show = TRUE) %>%
  bb_y_axis(tick = list(format = suffix("TWh")),
            label = list(text = "production (in terawatt-hours)", position = "outer-top")) %>%
  bb_legend(position = "inset", inset = list(anchor = "top-right")) %>%
  bb_labs(title = "Renewable energy production",
          caption = "Data source: RTE (https://opendata.rte-france.com)")
```

billboarder	<i>Create a Billboard.js widget</i>
-------------	-------------------------------------

Description

Create an interactive visualization with Javascript library Billboard.js

Usage

```
billboarder(
  bb_opts = list(),
  data = NULL,
  width = NULL,
  height = NULL,
  elementId = NULL
)
```

Arguments

bb_opts	A list in JSON format with chart parameters, see https://naver.github.io/billboard.js/demo/ .
data	A data.frame.
width	A numeric input in pixels.
height	A numeric input in pixels.
elementId	Use an explicit element ID for the widget.

billboarder-exports	<i>billboarder exported operators and S3 methods</i>
---------------------	--

Description

The following functions are imported and then re-exported from the billboarder package to avoid listing the magrittr as Depends of billboarder

billboarder-shiny *Shiny bindings for billboarder*

Description

Output and render functions for using billboarder within Shiny applications and interactive Rmd documents.

Usage

```
billboarderOutput(outputId, width = "100%", height = "400px")

renderBillboarder(expr, env = parent.frame(), quoted = FALSE)

billboarderProxy(
  shinyId,
  data = NULL,
  session = shiny::getDefaultReactiveDomain()
)
```

Arguments

outputId	output variable to read from
width, height	Must be a valid CSS unit (like '100%', '400px', 'auto') or a number, which will be coerced to a string and have 'px' appended.
expr	An expression that generates a billboarder
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.
shinyId	single-element character vector indicating the output ID of the chart to modify (if invoked from a Shiny module, the namespace will be added automatically)
data	A data.frame.
session	the Shiny session object to which the chart belongs; usually the default value will suffice

See Also

[proxy_example](#)

Examples

```
if (interactive()) {
  library(shiny)

  ui <- fluidPage(
    tags$h2("Include billboard charts in Shiny"),
```

```

fluidRow(
  column(
    width = 6,
    billboarderOutput("mybb1"),
    tags$p("Click on a bar to get the value:"),
    verbatimTextOutput("res_click")
  ),
  column(
    width = 6,
    billboarderOutput("mybb2")
  )
)
)

server <- function(input, output, session) {

  output$mybb1 <- renderBillboarder({

    dat <- data.frame(
      label = paste("Label", 1:5),
      value = sample.int(100, 5)
    )

    billboarder() %>%
      bb_barchart(
        data = dat,
        mapping = bbaes(label, value),
        rotated = TRUE
      )
  })

  output$res_click <- renderPrint({
    input$mybb1_click
  })

  output$mybb2 <- renderBillboarder({

    data(AirPassengers)

    air_passengers <- data.frame(
      date = as.Date(paste(
        rep(1949:1960, each = 12),
        rep(1:12, times = 12),
        "01", sep = "-"
      )),
      passengers = AirPassengers
    )

    billboarder() %>%
      bb_linechart(
        data = air_passengers,
        mapping = bbaes(date, passengers), type = "spline"
      )
  })
}

```

```
    ) %>%  
    bb_x_axis(tick = list(format = "%Y", fit = FALSE))  
  })  
}  
  
shinyApp(ui, server)  
}
```

cdc_prod_filiere *French electricity generation by power source for the day of 2017-06-12.*

Description

Average power generation (MW) per 30-minute interval within continental France, aggregated by broad power source. Last update : 2017-07-27.

Usage

```
cdc_prod_filiere
```

Format

A data frame with 48 rows and 11 variables:

date_heure Timestamp (POSIXct)

prod_total Total production in MW (thermal + hydro + nuclear + solar + wind + bioenergy)

prod_gaz Gas production in MW

prod_bioenergies Bioenergy production in MW

prod_hydraulique Hydraulic production in MW

prod_thermique_fossile Fossil thermal production in MW

prod_charbon Coal production in MW

prod_eolien Wind production in MW

prod_solaire Solar production in MW

prod_nucleaire Nuclear production in MW

prod_fioul Oil production in MW

Source

RTE

equilibre_mensuel *Monthly supply / demand balance (january 2007 to june 2017)*

Description

Monthly history of supply/demand balance (GWh) based on gross consumption, the balance of physical exchanges with foreign countries and offtakes due to pumping. Last update : 2017-07-27.

Usage

equilibre_mensuel

Format

A data frame with 126 rows and 5 variables:

date Date
solde Supply/demand balance (in GWh)
production Generation (in GWh)
pompage Pumping for hydraulic generation (in GWh)
consommation Consumption (in GWh)

Source

RTE (<https://odre.opendatasoft.com/explore/dataset/equilibre-national-mensuel-prod-conso-brute/>)

prefix *Shortcut to add a prefix value to axis labels*

Description

Shortcut to add a prefix value to axis labels

Usage

prefix(x)

Arguments

x A character of length one.

See Also

suffix

prod_filiere_long *French electricity generation by year and branch.*

Description

Annual French electricity production (TWh) by branch. Last update : 2017-02-15.

Usage

prod_filiere_long

Format

A data frame with 45 rows and 3 variables:

annee Year

branche Source of production

prod Production in TWh

Source

RTE (<https://odre.opendatasoft.com/explore/dataset/prod-national-annuel-filiere/>)

prod_par_filiere *French electricity generation by year and branch.*

Description

Annual French electricity production (TWh) by branch. Last update : 2017-02-15.

Usage

prod_par_filiere

Format

A data frame with 5 rows and 11 variables:

annee Year

prod_total Total production in TWh (thermal + hydro + nuclear + solar + wind + bioenergy)

prod_therm Thermal production in TWh (oil + gas + coal)

prod_hydraulique Hydraulic production in TWh

prod_bioenergies Bioenergy production in TWh

prod_eolien Wind production in TWh

prod_therm_charbon Coal thermal production in TWh

prod_solaire Solar production in TWh

prod_therm_gaz Gaz thermal production in TWh

prod_nucleaire Nuclear production in TWh

prod_therm_fioul Oil thermal production in TWh

Source

RTE (<https://odre.opendatasoft.com/explore/dataset/prod-national-annuel-filiere/>)

proxy_example

Proxy use example

Description

Launch an example to demonstrate how to use proxy method from billboarder in Shiny app.

Usage

```
proxy_example(chart = "gauge")
```

Arguments

chart Chart type for which to see an example, possible values are gauge, pie, bar, bar2, line, line2, density, histogram, lollipop, stacked_bar.

Examples

```
if (interactive()) {  
  
  # Titanic passenger  
  proxy_example("bar")  
  
  # Electricity production by sources and year  
  proxy_example("bar2")  
  
  # Moving lollipop with mpg dataset from ggplot2  
  proxy_example("lollipop")  
  
  # Update a stacked bar chart  
  proxy_example("stacked_bar")  
  
  # Moving sine and cosine  
  proxy_example("line")  
  
  # Changing lines and adding ones  
  proxy_example("line2")  
}
```



```
# Update pie chart
proxy_example("pie")

# Density with ggplot2 diamonds
proxy_example("density")

# Histogram with ggplot2 diamonds
proxy_example("histogram")

}
```

suffix

Shortcut to add a suffix value to axis labels

Description

Shortcut to add a suffix value to axis labels

Usage

```
suffix(x)
```

Arguments

x A character of length one.

See Also

prefix

Index

- * **datasets**
 - avengers, [4](#)
 - cdc_prod_filiere, [69](#)
 - equilibre_mensuel, [70](#)
 - prod_filiere_long, [71](#)
 - prod_par_filiere, [71](#)
- %>% (billboarder-exports), [66](#)
- aes (billboarder-exports), [66](#)
- avengers, [4](#)
- avengers_wide (avengers), [4](#)

- bauge, [5](#)
- bauge-shiny, [7](#)
- baugeOutput (bauge-shiny), [7](#)
- bb_add_style, [7](#), [54](#)
- bb_aes (billboard-aes), [63](#)
- bb_aes_string (billboard-aes), [63](#)
- bb_area, [8](#)
- bb_axis, [9](#)
- bb_bar, [10](#)
- bb_bar_color_manual, [12](#)
- bb_barchart, [10](#)
- bb_bubble, [13](#)
- bb_callbacks, [14](#)
- bb_categories, [15](#)
- bb_color, [16](#)
- bb_colors_manual, [17](#)
- bb_data, [18](#)
- bb_densityplot, [19](#), [27](#)
- bb_donut, [20](#)
- bb_donutchart, [21](#)
- bb_export, [22](#)
- bb_gauge, [23](#)
- bb_gaugechart, [24](#)
- bb_grid, [25](#)
- bb_histogram, [19](#), [26](#)
- bb_interaction, [28](#)
- bb_labs, [29](#), [59](#)
- bb_legend, [30](#)

- bb_line, [31](#)
- bb_linechart, [31](#)
- bb_load, [34](#)
- bb_lollipop, [35](#)
- bb_padding, [36](#)
- bb_pie, [37](#)
- bb_piechart, [38](#)
- bb_point, [39](#)
- bb_proxy_axis_labels, [39](#)
- bb_proxy_data_colors, [40](#)
- bb_proxy_data_names, [41](#)
- bb_proxy_defocus (bb_proxy_focus), [44](#)
- bb_proxy_flow, [43](#)
- bb_proxy_focus, [44](#)
- bb_proxy_groups, [46](#)
- bb_proxy_hide, [46](#), [49](#)
- bb_proxy_legend, [47](#)
- bb_proxy_show, [47](#), [49](#)
- bb_proxy_tooltip, [50](#)
- bb_proxy_transform, [50](#)
- bb_proxy_xs, [51](#)
- bb_radar, [51](#), [52](#)
- bb_radarchart, [52](#)
- bb_regions, [53](#)
- bb_render, [55](#)
- bb_scatterplot, [56](#)
- bb_spline, [57](#)
- bb_subchart, [57](#)
- bb_svg, [58](#)
- bb_title, [59](#)
- bb_tooltip, [59](#)
- bb_transition, [60](#)
- bb_treemap, [61](#), [62](#)
- bb_treemapchart, [61](#)
- bb_unload, [62](#)
- bb_x_axis (bb_axis), [9](#)
- bb_x_grid (bb_grid), [25](#)
- bb_y_axis (bb_axis), [9](#)
- bb_y_grid (bb_grid), [25](#)

bb_zoom, 63
bbaes, 11, 19, 21, 27, 32, 35, 38, 52, 56, 62
bbaes (billboard-aes), 63
bbaes_string (billboard-aes), 63
billboard-aes, 63
billboard-theme, 65
billboarder, 22, 37, 55, 66
billboarder-exports, 66
billboarder-package, 3
billboarder-shiny, 67
billboarderOutput (billboarder-shiny),
67
billboarderProxy, 11, 18, 21, 22, 25, 32, 37,
38, 54-56
billboarderProxy (billboarder-shiny), 67
cdc_prod_filiere, 69
density, 19
equilibre_mensuel, 70
geom_histogram, 27
JS (billboarder-exports), 66
prefix, 70
prod_filiere_long, 71
prod_par_filiere, 71
proxy_example, 67, 72
renderBauge (bauge-shiny), 7
renderBillboarder (billboarder-shiny),
67
set_color_palette (billboard-theme), 65
set_theme (billboard-theme), 65
suffix, 73